



99.95 EUR  
incl. 19% VAT, plus [shipping](#)

- Firmware 1104355, Rev A
- Full-size Mini-PCle !
- UMTS / 3G !
- 4G / LTE !



Latest firmware is installed : Generic SWI9X30C\_02.33.03.00 002.072\_000 GCF and PTCRB Approved—Release 27

#### AirPrime MC7455 M2M Module

Optimized 4G LTE Cat-6 IoT connectivity with 3G fallback for the EMEA. The MC7455 module is part of the MC Series offering unprecedented LTE speeds, bandwidth, and network performance on the PCI Express Mini Card form factor commonly used in networking equipment.

This LTE-Advanced Cat-6 embedded module delivers up to 300 Mbps download speed and supports most 4G LTE bands in Europe. With automatic fallback to 3G networks and integrated GNSS receiver (GPS, GLONASS, Beidou, and Galileo satellite systems supported), the MC7455 is ideal for networking and telematics applications.

- Dual SIM single standby (DSSS) switches between networks quickly to stay connected
- Switch networks anytime with up to three different certified firmware variants on board
- FREE unlimited firmware over-the-air (FOTA) upgrades future-proof deployments and keep them secure
- Securely collect data and remotely manage your IoT deployments with integrated [AirVantage®](#) cloud services
- GNSS receiver enables tracking and location-based services
- Embedded stack to easily communicate over the internet
- Basic and Extended AT Commands simplify development
- Tested for harsh environments and extreme temperatures

4G LTE	
Category	Cat-6

Frequency Bands	B1, B2, B3, B4, B5, B7, B8, B12, B13, B20, B25, B26, B29, B30, B41
<b>3G</b>	
WCDMA	B1, B2, B3, B4, B5, B8
<b>DATA SPEED</b>	
Peak Download Rate	300Mbps
Peak Upload Rate	50Mbps
<b>LOCATION SERVICES</b>	
Satellite Systems	Galileo, Glonass, GPS, Beidou
<b>EMBEDDED SOFTWARE</b>	
Firmware	Secure boot, Pre-certified firmware
System Drivers	Windows® 7, Windows® 8, Windows® 8.1, Windows® 10, Linux Driver: Standard ECM, Android RIL
<b>INTERFACES</b>	
Socket format	MiniPCIe
USB	USB 3.0, USB 2.0 High Speed
GPIO	4
SIM interface 1.8V/3V	1
<b>CONTROL OPTIONS</b>	
Commands	APIs, AT Commands
<b>HARDWARE</b>	
Dimensions	51x30x2.7mm
Antenna	Diversity, MIMO, GNSS Bias, Connectors: Main, Aux/GNSS, GNSS
Temperature Range	Industrial Grade: -40°C / + 85°C
<b>APPROVALS</b>	
Carrier	AT&T, Bell, Rogers, SouthernLINC, Sprint, T-Mobile, Telus, Verizon, Vodafone, US Cellular
Planned Carrier	KDDI, Rogers
Regulatory	CE, FCC, GCF, IC, NCC, PTCRB
<b>CLOUD SERVICES</b>	
	Free Unlimited FOTA upgrades, Connectivity Management option, Device Management option